

## SPECIFICATIONS

Insertion Cable	Outer Diameter	4mm/6mm
	Length	1.5M/3M
	Material	Tungsten
	Waterproof	No (IP65)
	Oilproof	No (IP65)
Probe	Field Of View	60° or 80°
	F No.	F4.0
	Depth Of View	15mm - ∞
	Illumination	4 to 6 High Intensity - LEDs
Articulation	Bend Angle	Higher than 90° bend
	Operation	Manual Joystick Control
LCD Monitor		3.5 Inch Color Digital TFT LCD
Light Adjustments		5 Levels
Zoom		5X
Record/Still Capture Function		Still Image
		Real Time Recording
Input/Output	Video Output (NTSC/PAL)	NTSC/PAL Output
	USB Port	USB Data Comm. Interface
Storage Media	USB Data Transportation Port	Micro SD Card (8GB Max)
	Still Image	JPG 640 x 480 pixel
	Video	AVI 640 x 480 pixel 15-30 fps
Playback Function		Still Image: Thumbnail 6-Image Display Full Screen Display Video: Play/Pause
Menu Operation		Date Pattern Selection
		Delete Stored Image
		Time & Date Setting
		Languages: English/Chinese/German/French
Ambient Working Temperature		USB Large Capacity Memory -10°C - 50°C
Power Supply	DC	4 AA Batteries - 5V DC
	AC	100V - 240V AC Adapter
Operating Time		Max 2 hours (with batteries)
Weight		590g
Carrying Case Size		470mm x 360mm x 150mm